# Elevator Belting Replacement. Parts. Accessories.



Bi-State Rubber offers multiple styles of replacement elevator belting in a multi-ply and single-ply carcass design for both rubber and PVC. Belting compounds range from standard Gr-2, Fire Resistant, High Temp, and MOR. Base belting tensions range from 120 PVC to over 1200 PIW for high capacity elevators. Belts will be custom punched to your bucket pattern. Fully assembled belts also available!



Inquire today about our fully assembled Elevator Belts complete with buckets and hardware attached!





#### **Buckets:**

Elevator Buckets are available in a wide variety of materials including fabricated steel, cast iron, nylon, and polyurethane.







#### Accessories:

We offer all needed hardware for bucket replacement and splicing.

Hardware:



Splices:





### Worksheet

## **Elevator Belting**

Address:	Date: Phone: Postal Fax:	Code:
HOLE PATTERN (Circle One)  • • • P1  • • • P2	Belt Width: Belt Length: Belt Tension: Cover Thickness: Top Bottom Belt Type: PVC RUBBER OTHER Rubber Abrasion High Fire Oil Other: Compound: Resistant Temp. Resistant Resistant Compound: Resistant	BUCKET STYLE (Circle)  Fabricated Steel Nylon  Cast Iron Polyurethane  Other:
••••• P3 P4 P5	CENTERED BUCKETS (Complete each box)  Row Centers  Bucket Spacing	Plate Butt Fasteners Splice  Overlap Clamp Splice Splice  Other:
•••••• P7  •••••• P8  P9	Holes to Edge of Belt  STAGGERED BUCKETS (Complete each box top and bottom)  Inside Holes	ADDITIONAL NOTES  Fully assembled belt needed:  YES   NO  Delivery needed by: (Date)  Comments:
OTHER: (Provide description)	Offset Hole Spacing	

Fax: 636-349-2393 sales@bistaterubber.com www.BISTATERUBBER.com



Ph: 636-349-2388